

**Description of Equipment:**

Ranger DX800R S5 - 1

Altitude -- 1000 to 1500 meters above sea level

Drill steel -- Ø51 mm (2") rods / T51

Drill steel length -- 4270 mm (14')

Drill steel type -- MF-rods

Manual languages -- English

Rotation motor -- OMT315 for 89-102 mm (3½"-4") holes

**Basic Unit**

1 pc Rock drill HL 820 T, hydraulic

1 pc Chain feed CF 145H with movable drill steel support

1 pc Rod handler RH 714 incl. 1 set of jaws

1 pc Boom DB 800 H, articulated

1 pc Carrier track mounted, turnable superstructure

1 pc Power pack diesel driven, hydraulic pumps and on-board compressor with twin pressure control

1 pc Control system Rock Pilot+, full radio remote

1 pc Dust collection system DC 810 H, hydraulic, Primary separator

9 pcs Working lights

1 pc Gauge set for accumulator pressure checking

1 pc Alarm signal

1 Set Manuals, paper copy

1 Set Manuals, USB memory

1 pc Alarm beacon

1 pc Hose reel

1 pc Service light, hand held 12V magnetic

EU-safety devices, EN16228

**Options**

Fuel powered heater for engine and water tank

TIM 5300 for vertical holes and depth measuring

Feed 5 485 mm (18'), without hose reel and horizontal drilling

Thread greasing with 5 gallon bucket

Anti- freeze system for air lines

Guides for grousers, long

Hydraulic rear ground support

Hydraulic winch

Led lights, 6 pcs

Turnable superstructure 180 deg.

Flushing control automatics

Shut down of suction for water holes

Water injection system

My Sandvik and SanRemo - select level from extra item

Spare radio remote transmitter

**Extra items**