

Description of Equipment:

Ranger DX900i T4-1
Alternative drill steel -- Ø51 mm (2") rods / T51
Altitude -- 1000 to 1500 meters above sea level
Drill steel -- Ø60 mm (2 $\frac{3}{8}$ ") rods / GT60
Drill steel type -- MF-rods
Flushing housing -- RD92x - 70 - Only 60mm drill steel
Lowest starting temperature -- Above 0 degrees
Manual languages -- English
Rotation motor -- OMT500 for 102-140 mm holes

Basic Unit

1 pc Rock drill RD927L, hydraulic with SLU system
1 pc CylF 16 feed HR, With hose reel
1 pc Rod handler RC1712 incl. 1 set of jaws
1 pc BoomDB5200, articulated
1 pc Carrier track mounted, Rotating upper structure CW180+CCW110 Degrees
1 pc Power pack diesel driven, hydraulic pumps and on-board compressor with twin pressure control
1 pc Control system iTorque, incl Flushing control automatics, Shutdown of suction for waterholes
1 pc TIMi for vertical holes and depth measuring
1 pc Operator's cabin F.O.P.S. and R.O.P.S. with Intelligent air condition safety +
1 pc Radio, 12V with USB MP3 Bluetooth, without CD
1 pc Dust collection system DC 900 H, hydraulic, Primary separator
1 pc Flushing control automatics
1 pc Shut down of suction in water holes
10 pcs Working lights, Halogen
1 pc Gauge set for accumulator pressure checking
1 pc Alarm signal
1 Set Manuals, paper copy
1 Set Manuals, USB memory
1 pc Alarm beacon
1 pc Service light
SanRemo Mobile, Bluetooth connectivity
EU-safety devices, EN16228

Options

Electric hydraulic oil filling pump
Guides for grousers, long
Hydraulic rear ground support
Hydraulic winch with full radio drilling, tramming boom and rod handling
Towing hook
Led lights 17 pcs. also carrier rear and side option lights
Alternative seat with 3-point seat belt and air cushioning
H13 Cabin filter, HEPA
Radio CD/MP3 Bluetooth, Handsfree, DAB
Reversing camera
Roller blinds for cabin windows
Vacuum cleaner for cabin
Explosion proof cabin window
Automatic feed alignment for TIMi
TIMi for inclined holes with TIM3D readiness
RockPulse sensor system
Kit for alternative steels, each
Thread greasing
Long feed for 14' rods, CylF 18 HR, not with horizontal drilling
Full cycle one hole automatic drilling
CSL-system for R92x series rock drill, replaces standard component
Cold-weather package -25degree, incl watertank heater
Dustmizer requires flap feeder (engine heater option needed below freezing point)
Flap feeder for dust collector
Water injection system
My Sandvik and SanRemo - select level from extra item

Extra items
